

O'NEILL  
Serial No. Unknown

4. (Amended) A method according to claim 1, comprising generating said first routing protocol data prior to mobility of said mobile node from said first access node to said second access node.

5. (Amended) A method according to claim 1, wherein said second protocol data includes data indicating that said second protocol data results from mobility of said mobile node.

7. (Amended) A method according to claim 1, comprising limiting the storage of said second protocol data substantially to packet switching nodes located in the vicinity of a routing path between said second access node and said first access node.

8. (Amended) A method according to claim 1, comprising generating said second routing protocol data in response to a routing protocol control message injected from the second access node.

9. (Amended) A method according to claim 1, wherein said routing protocol data relates to a number of hops along a route to said mobile node and passing through an access node.

10. (Amended) A method according to claim 1, wherein said second set of packet switching nodes includes a subset of said first packet switching nodes, and said second routing protocol data is used in preference to said first routing protocol data to determine a next-hop routing decision in a packet switching node holding both said first routing protocol data and said second routing protocol data.

11. (Amended) A method according to claim 1, comprising, when routing a packet destined for said first network address, routing said packet, from a packet switching node having a plurality of adjacent packet switching nodes including at least

O'NEILL  
Serial No. Unknown

one-of said first set of packet switching nodes and only one of said second set of packet switching nodes, to said one of said second set of packet switching nodes in preference to said at least one of said first set of packet switching nodes.

12. (Amended) A method according to claim 1, comprising routing packets destined for said first network address via at least one of said first set of packet switching nodes and at least one of said second set of packet switching nodes.

13. (Amended) A method according to claim 1, wherein said first and second routing protocol data relates to next-hop routing to packet switching nodes which are adjacent to the packet switching node in which the routing protocol data is held, said first routing protocol data relating to next-hop routing to a first plurality of packet switching nodes and said second data routing protocol data relating to next-hop routing to a second plurality of packet switching nodes, said first and said second pluralities being mutually exclusive.

14. (Amended) A method according to claim 1, comprising simultaneously holding said first and second, and third routing protocol data, for said first network address, said third routing protocol data relating to a third access node via which packets are currently to be transmitted to said mobile node using said first network address, in a third set, different to said first and second sets, of said packet switching nodes.


15. (Amended) A method according to claim 13, wherein said third routing protocol data relates to next-hop routing to packet switching nodes which are adjacent the packet switching node in which the routing protocol data is held, said third routing

O'NEILL  
Serial No. Unknown

protocol data relating to next-hop routing to a third plurality of packet switching nodes, said first, said second and said third pluralities being mutually exclusive.

16. (Amended) A method according to claim 14, wherein said third routing protocol data includes data which relates to said third access node and does not relate to said first and second access nodes.

17. (Amended) A method according to claim 14, wherein said first, second and third routing protocol data includes data indicating a sequence of mobility from said first access node to said second access node and from said second access node to said third access node.

 18. (Amended) A method according to claim 14, comprising, when routing a packet destined for said first network address, routing said packet, from a packet switching node having a plurality of adjacent packet switching nodes including at least one of said first set and/or said second set of packet switching nodes and only one of said third set of packet switching nodes, to said one of said third set of packet switching nodes in preference to said at least one of said first set and/or said second set of packet switching nodes.

19. (Amended) A method according to claim 14, comprising routing packets destined for said first network address via at least one of said first set of packet switching nodes, at least one of said second set of packet switching nodes, and at least one of said third set of packet switching nodes.

20. (Amended) A method according to claim 1, wherein said mobile node is connectable to an access node via a wireless link, said mobility involving handover of the mobile node at the wireless link layer.